



BLANKE BASEMAX

BLANKE BASEMAX is a lightweight levelling compound used to create an even composite substrate prior to laying BLANKE PERMAT, BLANKE PERMATFLOOR and BLANKE PERMATOP. The 2-component system consists of a lightweight filler made of expanded glass granulate and a cementitious binder. This lightweight levelling compound makes it possible to level uneven surfaces from 5 to 100 mm in indoor areas. It is particularly lightweight, quick drying and ready for laying coverings on after just 12 hours. Subsequently, it is possible to quickly install a tiled surface on the Blanke products BLANKE PERMAT, BLANKE PERMATFLOOR and BLANKE PERMATOP.

Advantages:

- > Mixing ratio by weight 1:1
- > Lightweight, low static load
- > Good coverage due to high proportion of lightweight ingredients
- > 2-component mix creates permanent, secure bonding
- > Quick drying
- > Ready for laying after 12 hours

Expert tip:

- > The structure of the filler ensures a very low mass per unit area. BLANKE BASEMAX is approx. 75% lighter than conventional screeds.
- > Pipes/cables previously laid on the bare floor can be incorporated or seated appropriately.

BLANKE BASEMAX

COMPONENT A (BINDER)

1 bag of 25 kg, mixing ratio

A+B by weight 1:1 PU: 1 bag

Art. no.	€/kg
288-900	6.34

BLANKE BASEMAX

COMPONENT B (LIGHTWEIGHT FILLER)

1 bag of 12.5 kg, mixing ratio

A+B by weight 1:1 PU: 1 bag

Art. no.	€/kg
287-900	6.34

